



EN ISO 20345:2011


 HORIZON
GAMMA
 52421-01L

S3 *CI SRC
Size: 36-48
Weight: 760 gr.

Fit: 10,5

Working Environment:
 Building, Wood-metal carpentry,
 Farming and Gardening,
 Engineering


FEATURES

UPPER

 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Reflex insert

LINING

 Soft Full Grain Leather Hydro
 Double non-slip layer of
 microfibre, resistant up to 200,000
 cycles. Makes the footwear more
 comfortable, blocking the foot
 during use.

INSOLE

Climaction-Fit 337

TOE CAP

Steel Toe Cap

RESISTANCE TO PERFORATION

Steel Plate

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

 Two-component PU sole with self-
 cleaning pattern, extremely flexible
 for various places of use, both
 indoor and outdoor, with SRC
 Antislip Standard.

TECHNOLOGIES

Removable Insole

climaction fit

 Removable anatomic and ergonomic
 insole. Absorbent and transpiring
 open-cell foam support. Keeps feet
 fresh. Specifically-designed
 thermoforming for exceptional
 comfort.


Protection elements

STEEL PROTECTION

 Steel toecap, with anti-corrosion
 paint. Protection of over 200J.
 Comfortable fit. Stainless steel Plate
 resistant puncture with acid-resistant
 paint.



Lateral stability

dynamic HC control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

 It supports the heel bone, the instep
 and tarsal joints, without altering
 energy absorption. A support for the
 natural movement of the foot; it
 provides comfort and greater
 stability.


Electrical features

WED

Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other

DUAL MICRO
DRY WICKO

 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


SRC (SRA+SRB)


 SOLE 52 - 53
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.36
	HEEL (CONTACT ANGLE °) ≥ 0.28	0.42
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL (CONTACT ANGLE °) ≥ 0.13	0.14

EN ISO 20344:2011