



EN ISO 20344:2011



HORIZON
ILLINOIS
53023-13

S2 SRC

Size: 36-48
Weight: 610 gr.

Fit: 10,5

Working Environment:
Multipurpose, Wood-metal carpentry, Logistics and Light Industry, Farming and Gardening



FEATURES

TOMAIA
Grain leather Hydro 1,8-2,0 mm
Fabric of High Tenacity

FODERA
3D Air circulation 320 gr.

SUOLETTA
Climaction-Fit 337



PUNTALE
Steel Toe Cap

TIPOLOGIA
Ankle boot

SUOLA
PU DUAL-DENSITY SRC
Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.



SRC (SRA+SRB)

		SOLE 52 - 53 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.36 0.42
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.14

EN ISO 20344:2011

TECNOLOGIE

Suoletta Intercambiabile
337
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements

STEEL TOECAP

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit, with compensation rubber.




Lateral stability
dynamic HC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUALMICRO DUALWICBO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.