



EN ISO 20345:2011


 HORIZON  
**ILLINOIS**  
 52023-15L

**S3 \*CI SRC**
**Size:** 36-48  
**Weight:** 700 gr.

**Fit:** 10,5

**Working Environment:**  
 Multipurpose, Building, Logistics  
 and Light Industry, Farming and  
 Gardening


## FEATURES

### UPPER

 Grain leather Hydro 1,8-2,0 mm  
 Fabric of High Tenacity

### LINING

3D Air circulation 320 gr.

### INSOLE

Climaction-Fit 337

### TOE CAP

Steel Toe Cap

### RESISTANCE TO PERFORATION

Steel Plate

### TYPE

Ankle boot

### SOLE

#### PU DUAL-DENSITY SRC

Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

## TECHNOLOGIES

### Removable Insole

#### 337 climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



### Protection elements

#### STEEL PROTECTION

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit. Stainless steel Plate resistant puncture with acid-resistant paint.



### Lateral stability

#### dynamic HC control technology


Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

#### STABIL•ACTIVE

It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features

#### WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other

#### DUAL MICRO DWT WICBO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



## SRC (SRA+SRB)


 SOLE 52 - 53  
 PU - PU

<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.36</b> <b>0.42</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.19</b> <b>0.14</b>

EN ISO 20344:2011