



EN ISO 20344:2011

HORIZON

JESI

52092-02L

S1P SRC

Size: 36-48

Weight: 620 gr.

Fit: 10,5

Working Environment:

Multipurpose, Building, Logistics and Light Industry, Farming and Gardening

FEATURES

UPPER

nubuk-look leather Hydro
3D Air circulation 320 gr.

LINING

3D Air circulation 320 gr.

INSOLE

Flyfit

TOE CAP

Steel Toe Cap

RESISTANCE TO PERFORATION

Steel Plate

TYPE

Sandal

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

TECHNOLOGIES

Removable Insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.



Protection elements

STEEL PROTECTION

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit. Stainless steel Plate resistant puncture with acid-resistant paint.



SRC (SRA+SRB)



SOLE 52 - 53
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.36
	HEEL (CONTACT ANGLE 7°) ≥ 0.28	
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL (CONTACT ANGLE 7°) ≥ 0.13	

EN ISO 20344:2011

Lateral stability

dynamic **HC** control
technology


Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUAL MICRO DWT MICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.