

EN ISO 20344:2011



HORIZON
KENTUCKY
53022-12L

S3 SRC

Size: 36-48
Weight: 640 gr.

Fit: 10,5

Working Environment:
Multipurpose, Building,
Engineering, Farming and
Gardening

FEATURES

UPPER

Grain leather Hydro 1,8-2,0 mm
Fabric of High Tenacity

LINING

3D Air circulation 320 gr.

INSOLE

Basic

TOE CAP

Steel Toe Cap

RESISTANCE TO PERFORATION

Steel Plate

TYPE

Low Shoe

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

TECHNOLOGIES

Removable Insole

BASIC

Antistatic absorbent in foamed latex insole



Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

Double non-slip layer of microfibre, resistant up to 200000. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)



SOLE 52 - 53
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.36
	HEEL (CONTACT ANGLE °°) ≥0.28	0.42
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE °°) ≥0.13	0.14

EN ISO 20344:2011