



EN ISO 20345:2011



HORIZON
STEEL
52440-00L

S3 SRC

Size: 36-48
Weight: 770 gr.

Fit: 10,5

Working Environment:
Building, Wood-metal carpentry,
Farming and Gardening,
Multipurpose



FEATURES

UPPER

Grain leather Hydro 1,8-2,0 mm
Reflex insert

LINING

Breezy 3D, two-layers
combination
Double non-slip layer of
microfibre, resistant up to 200,000
cycles. Makes the footwear more
comfortable, blocking the foot
during use.

INSOLE

Climaction-Fit 337

TOE CAP

Steel Toe Cap

RESISTANCE TO PERFORATION

Steel Plate

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with self-
cleaning pattern, extremely flexible
for various places of use, both
indoor and outdoor, with SRC
Antislip Standard.

TECHNOLOGIES

Removable Insole

337 climaction fit

Removable anatomic and ergonomic
insole. Absorbent and transpiring
open-cell foam support. Keeps feet
fresh. Specifically-designed
thermoforming for exceptional
comfort.



Protection elements

STEEL PROTECTION

Steel toecap, with anti-corrosion
paint. Protection of over 200J.
Comfortable fit. Stainless steel Plate
resistant puncture with acid-resistant
paint.



Lateral stability

dynamic control technology


Ergonomic rigid structure. It
accommodates the heel, adjusting the
foot support and control of the ankle
in sideways movements. The plastic
material increases protection of the
ankle against sharp or pointy objects.



Torsional stability

STABIL•ACTIVE

It supports the heel bone, the instep
and tarsal joints, without altering
energy absorption. A support for the
natural movement of the foot; it
provides comfort and greater
stability.



Electrical features

WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,
ensuring proven anti-static properties
of the footwear over time.



Other

DUAL MICRO DUAL WICKO

Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.



SRC (SRA+SRB)



SOLE 52 - 53
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.36
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011