



EN ISO 20345:2011



HORIZON

VEGA
52045-02L
S3 SRC
Size: 36-48

Weight: 680 gr.

Fit: 10,5

Working Environment:

Multipurpose, Building,
Engineering, Farming and
Gardening

FEATURES

UPPER

Pigmented Leather-Hydro 1,8-2,0 mm
Reflex insert

LINING

3D Air circulation 320 gr.
Double non-slip layer of
microfibre, resistant up to 200,000
cycles. Makes the footwear more
comfortable, blocking the foot
during use.

INSOLE

Basic

TOE CAP

Steel Toe Cap

RESISTANCE TO PERFORATION

Steel Plate

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with self-
cleaning pattern, extremely flexible
for various places of use, both
indoor and outdoor, with SRC
Antislip Standard.

TECHNOLOGIES

Removable Insole

BASIC

Antistatic absorbent in foamed latex
insole


Protection elements

STEEL PROTECTION

Steel toecap, with anti-corrosion
paint. Protection of over 200J.
Comfortable fit. Stainless steel Plate
resistant puncture with acid-resistant
paint.



Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

It supports the heel bone, the instep
and tarsal joints, without altering
energy absorption. A support for the
natural movement of the foot; it
provides comfort and greater
stability.


Electrical features

WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,
ensuring proven anti-static properties
of the footwear over time.


Other

DUAL MICRO DUAL MICRO

Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.


SRC (SRA+SRB)


SOLE 52 - 53
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.36
	HEEL (CONTACT ANGLE °) ≥0.28	0.42
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE °) ≥0.13	0.14

EN ISO 20344:2011