



EN ISO 20344:2011



JUST GRIP
AUCKLAND HIGH
98405-02L

S3 HRO HI SRC

Size: 38-48
Weight: 595 gr.

Fit: 11

Working Environment:
Logistics and Light Industry,
Components and Automotive,
Ho.Re.Ca., ESD Areas



FEATURES

UPPER

Digitex Airy
MicroFiber Suede 1,6-1,8 mm
Digitex Hydro Airy
MicroFiber Suede with Pro-tech
SXT light 1,6-1,8 mm

LINING

Breezy 3D, two-layers
combination

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU-RUBBER VIBRAM "COLTELLO DESIGN"

Light and comfortable PU
midsole. VIBRAM, COLTELLO,
rubber outsole, designed for
particularly slippery and wet work
conditions. Extraordinary grip
performance and excellent
comfort.

TECHNOLOGIES

Removable Insole



Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"



Protection elements



RESISTANT
TO 3.0 mm.
NAILS



Toecap "Alu Sxt 2.0" with
differentiated thicknesses, resistant
to 200J. Non metal perforation
resistant Insert to over 1100 N with a
3.0 mm truncated cone nail. Protection
over the entire sole of the foot.
Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability



Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features




ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other



Created for those who work in the
HORECA sector, H.ABC footwear has
new antibacterial components
subjected to analysis by accredited
laboratories. The results confirm the
constant elimination activity of over
80% of bacterial load.



SRC (SRA+SRB)



SOLE 98
PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.49
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.27
		0.26

EN ISO 20344:2011