



EN ISO 20344:2011



JUST GRIP  
**NEWPORT BOA**  
98379-04L

**S3 HRO HI SRC**

**Size:** 38-48  
**Weight:** 600 gr.

**Fit:** 11

**Working Environment:**  
Logistics and Light Industry,  
Components and Automotive, ESD  
Areas, Ho.Re.Ca.



**FEATURES**

**UPPER**

Digitex Airy  
MicroFiber Suede 1,6-1,8 mm  
Digitex Hydro Airy  
MicroFiber Suede with Pro-tech  
SXT light 1,6-1,8 mm

**LINING**

Breezy 3D, two-layers  
combination

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

Five 4 Fit

**TOE CAP**

Alu SXT 2.0 Toe cap

**RESISTANCE TO PERFORATION**

KX Antiperforation PS

**TYPE**

Low Shoe

**SOLE**

**PU-RUBBER VIBRAM "COLTELLO DESIGN"**

Light and comfortable PU  
midsole. VIBRAM, COLTELLO,  
rubber outsole, designed for  
particularly slippery and wet work  
conditions. Extraordinary grip  
performance and excellent  
comfort.

**TECHNOLOGIES**

**Removable Insole**



Highly breathable and absorbent  
anatomic insole. Multilayer structure  
to take advantage of the peculiarities  
of each component. Dry and with a  
comfortable memory foam "pillow"



**Protection elements**



Toecap "Alu Sxt 2.0" with  
differentiated thicknesses, resistant  
to 200J. Non metal perforation  
resistant Insert to over 1100 N with a  
3.0 mm truncated cone nail. Protection  
over the entire sole of the foot.  
Flexible and comfortable



**Lateral stability**



Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.



**Torsional stability**



Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



**Electrical features**




ESD footwear discharge static  
electricity and avoid damaging  
surrounding objects; they are  
designed in compliance with the  
following standards: IEC EN  
61340-5-1:2016 - IEC EN  
61340-4-3:2018 - IEC EN  
61340-4-5:2018.

**Other**



Created for those who work in the  
HORECA sector, H.ABC footwear has  
new antibacterial components  
subjected to analysis by accredited  
laboratories. The results confirm the  
constant elimination activity of over  
80% of bacterial load.



**SRC (SRA+SRB)**



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.49
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.27
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011