



EN ISO 20345:2011


 JUST GRIP  
**RANDA**  
 98387-10L

**S3 HRO HI SRC**
**Size:** 38-48  
**Weight:** 590 gr.

**Fit:** 11

**Working Environment:**  
 Multipurpose, Logistics and Light Industry, Components and Automotive, Ho.Re.Ca.


## FEATURES

### TOMAIA

Drummed leather Hydro 1,8-2,0 mm

### FODERA

3D Air circulation 320 gr.

### FOD. ANTISCIVOLO

DUALMICRO

### SUOLETTA

Five 4 Fit

### PUNTALE

Alu SXT 2.0 Toe cap

### RESISTENZA ALLA

PERFORAZIONE

KX Antiperforation PS

### TIPOLOGIA

Low Shoe

### SUOLA

**PU-RUBBER VIBRAM "COLTELLO DESIGN"**

Light and comfortable PU midsole. VIBRAM, COLTELLO, rubber outsole, designed for particularly slippery and wet work conditions. Extraordinary grip performance and excellent comfort.

## TECNOLOGIE

### Suoletta Intercambiabile



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Elementi di Protezione

**ZERO(k)**  
 ANTIPERFORATION

**alu-sxt2.0**  
 aluminium

A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



### Stabilità Trasversale

**dynamic H.C control**  
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Stabilità Torsione

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Caratteristiche Elettriche




ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Altro

**SXT H.ABC**  
 HIGH ANTIBACTERIAL COMPONENT

Created for those who work in the HORECA sector, H.ABC footwear has new antibacterial components subjected to analysis by accredited laboratories. The results confirm the constant elimination activity of over 80% of bacterial load.



## SRC (SRA+SRB)



SOLE 98 PU - RUBBER		
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	<b>0.49</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	<b>0.27</b>

EN ISO 20344:2011