



EN ISO 20347:2022



JUST GRIP

**ROCK**
**18182-14L**
**O3S FO HI HRO SR**
**Size:** 35-48

**Weight:** 520 gr.

**Fit:** 11

**Working Environment:**

Finishing-off building, Logistics and Light Industry, Components and Automotive, ESD Areas



## FEATURES

### UPPER

 Nubuk Leather Hydro 1,6-1,8 mm  
 Soft Full Grain Leather Hydro

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Five 4 Fit

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

**PU-RUBBER VIBRAM "COLTELLO DESIGN"**

Light and comfortable PU midsole. VIBRAM, COLTELLO, rubber outsole, designed for particularly slippery and wet work conditions. Extraordinary grip performance and excellent comfort.

## TECHNOLOGIES

### Removable Insole

**FIVE 4 FIT**

Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Protection elements


 RESISTANT  
 TO 3.0 mm.  
 NAILS

EN ISO 20347:2012

"Occupational" footwear with all the physico-chemical characteristics and the comfort of Sixton footwear. Footwear without safety toecap, with non metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



### PU - RUBBER

SOLE 98

### SLIP RESISTANCE

EN ISO 20344:2021

**BASIC**  
 CERAMIC WITH  
 NALS

 FORWARD  
 HEEL SLIP  
 $\geq 0.31$   
 BACKWARD  
 FOREPART SLIP  
 $\geq 0.36$ 
**0,48**
**0,49**

**SR**  
 CERAMIC WITH  
 GLYCERINE

 FORWARD  
 HEEL SLIP  
 $\geq 0.19$   
 BACKWARD  
 FOREPART SLIP  
 $\geq 0.22$ 
**0,26**
**0,29**


### Lateral stability

**dynamic H C control**  
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability


**STABIL ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Other

"Occupational" footwear with all the physico-chemical characteristics and the comfort of Sixton footwear. Footwear without safety toecap, with no anti-perforation insert.