



EN ISO 20345:2011

JUST GRIP LADY

# ALA

99429-03

## **SBAEFOHROSRC**

Size: 35-42 Lady Weight: 425 gr.

Fit: 11

# Working Environment:

Food and Chemical industry, Ho.Re.Ca., ESD Areas











# **FEATURES**

#### **UPPER**

#### LINING

Bacteriostatic Teklife 3D

# **ANTISLIP LINING**

Five 4 Fit "lady"

Clogs

#### **SOLE**

### **PU-RUBBER VIBRAM®** "COLTELLO" SRC-HRO

Light and comfortable PU midsole.Vibram®, COLTELLO, rubber outsole, designed for particularly slippery and wet work conditions. Extraordinary grip performance and excellent comfort

# **TECHNOLOGIES**

### Removable Insole



Highly breathable and absorbent anatomic insole.Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

### **Protection elements**



The result of the evolution of the latest aluminium technologies. A new multi-thicknesses toe cap, which delivers a highly performing protection where needed. Ultralight protection, keeping comfortable inner



### Lateral stability

# dynamic H control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

# Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater



# **Electrical features**




ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.



# Other



Created for those who work in the HORECA sector, H.ABC footwear has new antibacterial components subjected to analysis by accredited laboratories. The results confirm the constant elimination activity of over 80% of bacterial load.



MicroFiber XPRO 1,8-2,0 mm

# **DUALMICRO**

# INSOLE

# **TOE CAP**

Alu SXT 2.0 Toe cap

# TYPE

# SRC (SRA+SRB)

