



EN ISO 20344:2011



JUST GRIP LADY

BOMA

99401-08L

S3 HRO HI SRC

Size: 35-42 Lady
Weight: 450 gr.

Fit: 11

Working Environment:

Logistics and Light Industry,
Components and Automotive,
Ho.Re.Ca., ESD Areas



FEATURES

UPPER

Drummed leather Hydro 1,8-2,0 mm

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit "lady"

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU-RUBBER VIBRAM "COLTELLO DESIGN"

Light and comfortable PU midsole. VIBRAM, COLTELLO, rubber outsole, designed for particularly slippery and wet work conditions. Extraordinary grip performance and excellent comfort.

TECHNOLOGIES

Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

Protection elements

ZERO(k)
ANTIPERFORATION



A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



Lateral stability

dynamic HC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features




ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



Created for those who work in the HORECA sector, H.ABC footwear has new antibacterial components subjected to analysis by accredited laboratories. The results confirm the constant elimination activity of over 80% of bacterial load.



SRC (SRA+SRB)



SOLE 99
PU - RUBBER

| SRA CERAMIC + DETERGENT SOLUTION | FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28 | 0.36 0.41 |
|--|---|--------------|
| SRB STEEL + GLYCEROL | FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13 | 0.31 0.28 |

EN ISO 20344:2011