

EN ISO 20345:2011



JUST GRIP LADY

**BOMA**

**99401-08L**

**S3 HRO HI SRC**

**Size:** 35-42 Lady

**Weight:** 450 gr.

**Fit:** 11

**Working Environment:**

Logistics and Light Industry,  
Components and Automotive,  
Ho.Re.Ca., ESD Areas



## FEATURES

### UPPER

Drummed leather Hydro 1,8-2,0 mm

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Five 4 Fit "lady"

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Low Shoe

### SOLE

**PU-RUBBER VIBRAM "COLTELLO DESIGN"**

Light and comfortable PU midsole. VIBRAM, COLTELLO, rubber outsole, designed for particularly slippery and wet work conditions. Extraordinary grip performance and excellent comfort.

## TECHNOLOGIES

### Removable Insole

**FIVE 4 FIT**  
LADY.

Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Protection elements

**ZERO(k)**  
ANTIPERFORATION

**alu-sxt2.0**  
aluminium

A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



### Lateral stability

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features




ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Other

**SXT H.ABC**  
HIGH ANTIBACTERIAL COMPONENT

Created for those who work in the HORECA sector, H.ABC footwear has new antibacterial components subjected to analysis by accredited laboratories. The results confirm the constant elimination activity of over 80% of bacterial load.



## SRC (SRA+SRB)

SOLE 99 PU - RUBBER		
<b>SRA</b> CERAMIC + DIETERY SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.36</b> <b>0.41</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.31</b> <b>0.28</b>

EN ISO 20344:2011