



EN ISO 20347:2012



JUST GRIP LADY

CIMA
19398-06
02 FO HRO HI SRC
Size: 35-42 Lady

Weight: 370 gr.

Fit: 11

Working Environment:

Multipurpose, Logistics and Light Industry, ESD Areas, Ho.Re.Ca.



FEATURES

UPPER

 Digitex Hydro Airy
 MicroFiber Suede 1,6-1,8 mm
 Digitex Hydro Airy
 MicroFiber Suede with Pro-tech
 SXT light 1,6-1,8 mm

LINING

 Breezy 3D, two-layers
 combination

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

TYPE

Low Shoe

SOLE

PU-RUBBER VIBRAM "COLTELLO DESIGN"

 Light and comfortable PU
 midsole. VIBRAM, COLTELLO,
 rubber outsole, designed for
 particularly slippery and wet work
 conditions. Extraordinary grip
 performance and excellent
 comfort.

TECHNOLOGIES

Removable Insole

FIVE 4 FIT

 Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"


Protection elements

EN ISO 20347:2012

 "Occupational" footwear with all the
 physico-chemical characteristics and
 the comfort of Sixton
 footwear. Footwear without safety
 toecap, with no anti-perforation
 insert.

Lateral stability

dynamic HC control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other

SXT H.ABC
 HIGH ANTIBACTERIAL COMPONENT

 Created for those who work in the
 HORECA sector, H.ABC footwear has
 new antibacterial components
 subjected to analysis by accredited
 laboratories. The results confirm the
 constant elimination activity of over
 80% of bacterial load.


SRC (SRA+SRB)


 SOLE 99
PU - RUBBER

| | | |
|--|-------------------------------------|------|
| SRA CERAMIC + DETERGENT SOLUTION | FLAT ≥0.32 | 0.36 |
| | HEEL (CONTACT ANGLE °°) ≥0.28 | 0.41 |
| SRB STEEL + GLYCEROL | FLAT ≥0.18 | 0.31 |
| | HEEL (CONTACT ANGLE °°) ≥0.13 | 0.28 |

EN ISO 20344:2011