



EN ISO 20345:2011



MODULAR BELLARIA

82297-05LM

S1P SRC**Size:** 36-48**Weight:** 600 gr.**Fit:** 11**Working Environment:**

Finishing-off building, Logistics and Light Industry, Components and Automotive, ESD Areas

**FEATURES****UPPER**

Drummed leather Hydro 1,8-2,0 mm
 Pu Coated Leather 1,8-2,0 mm
 MicroFiber Xtop 1,8-2,0 mm
 Mesh H.T. no ladder
 Reflex insert
 3D Air circulation 320 gr.

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Climaction-Fit 337

TOE CAP


Fiber cap SXT

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

TYPE

Sandal

**SRC (SRA+SRB)**

		SOLE 82	PU - PU	
SRA	SRB	FLAT ≥ 0.32	HEEL (CONTACT ANGLE °) ≥ 0.28	0.47
CERAMIC DETERGENT SOLUTION	STEEL GLYCEROL	FLAT ≥ 0.18	HEEL (CONTACT ANGLE °) ≥ 0.13	0.21 0.16

EN ISO 20345:2011

TECHNOLOGIES**Removable Insole**
climaction

337

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.

**Protection elements**
KX

RESISTANT TO 3.0 mm NAILS

alu-sxt

aluminium 2.0

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable

**Lateral stability**
dynamic HC control

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

**Torsional stability**
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

**Electrical features**

ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other
DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.