



EN ISO 20345:2011


 MODULAR
BELLUNO
82295-05LM
S3 *CI SRC
Size: 36-48
Weight: 650 gr.

Fit: 11

Working Environment:
 Finishing-off building, Logistics
 and Light Industry, Components
 and Automotive, ESD Areas


FEATURES

UPPER

 Drummed leather Hydro 1,8-2,0
 mm
 Pu Coated Leather 1,8-2,0 mm
 Reflex insert

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Climaction-Fit 337

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU / PU ESD-PLUS SRC

 Double density PU sole, Outer- and
 in-between sole with ESD
 compound. For use in contact with
 sensitive electronic equipment.
 Light and comfortable, very
 versatile, highly non-slip SRC
 Antislip standard.

TECHNOLOGIES

Removable Insole

337
climaction fit

 Removable anatomic and ergonomic
 insole. Absorbent and transpiring
 open-cell foam support. Keeps feet
 fresh. Specifically-designed
 thermoforming for exceptional
 comfort.


Protection elements

KX RESISTANT
 TO 3.0 mm.
 NAILS **fibercap sxt**

 Composite toecap with fiberglass.
 Resistant to over 200J. Non metal
 perforation resistant insert to over
 1100 N with a 3.0 mm truncated cone
 nail. Protection over the entire sole of
 the foot. Flexible and comfortable


Lateral stability

dynamic HC control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other

DUALMICRO
DRYWICKO

 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


SRC (SRA+SRB)


 SOLE 82
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.47
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.43
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.21
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.16

EN ISO 20344:2011