



EN ISO 20345:2011



MODULAR BELLUNO 83295-07LL

S3 *CI SRC
Size: 41-47 Modular-fit L
Weight: 610 gr.

Fit: 12,5

Working Environment:
 Finishing-off building, Logistics
 and Light Industry, Components
 and Automotive, ESD Areas


FEATURES

TOMAIA

 Drummed leather Hydro 1,8-2,0 mm
 Pu Coated Leather 1,8-2,0 mm
 Reflex insert

FODERA

3D Air circulation 320 gr.

FOD. ANTISCIVOLO DUALMICRO

SUOLETTA

Climaction-Fit 337

PUNTALE

Fiber cap SXT

RESISTENZA ALLA PERFORAZIONE

KX Antiperforation PS

TIPOLOGIA

Ankle boot

SUOLA

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

TECNOLOGIE

Suoletta Intercambiabile

337

climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Elementi di Protezione


 RESISTANT
TO 3.0 mm.
NAILS

fiber cap sxt

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Stabilità Trasversale

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Stabilità Torsione



STABIL ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Caratteristiche Elettriche



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Altro

DUALMICRO DUALWICKO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)


 SOLE 83
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.47
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.21
		0.16

EN ISO 20344:2011