



EN ISO 20345:2011



POLAR

## ADVENTURE

88039-00L

S3 \*CI HRO HI WR SRC

Size: 38-48

Weight: 780 gr.

Fit: 11

**Working Environment:**  
 Multipurpose, Farming and  
 Gardening, Farming and  
 Gardening, Oil industry


## FEATURES

### UPPER

No ladder H.T. Fabric  
 MicroFiber TOP 1,8-2,0 mm  
 Reflex insert

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

#### PU-RUBBER VIBRAM-HRO-SRC

Sole resistant to 300°C by contact.  
 With scaff cap and compound  
 designed with VIBRAM for stability  
 and grip performance. Outsole  
 designed to strike the ground  
 better and to improve self-  
 cleaning. With anti-wear scaff cap.

## TECHNOLOGIES

### Removable Insole

#### 337 climaction fit

Removable anatomic and ergonomic  
 insole. Absorbent and transpiring  
 open-cell foam support. Keeps feet  
 fresh. Specifically-designed  
 thermoforming for exceptional  
 comfort.


### Protection elements


RESISTANT  
 TO 3.0 mm.  
 NAILS

fibercap sxt

Composite toecap with fiberglass.  
 Resistant to over 200J. Non metal  
 perforation resistant insert to over  
 1100 N with a 3.0 mm truncated cone  
 nail. Protection over the entire sole of  
 the foot. Flexible and comfortable


### Lateral stability

#### dynamic HC control technology

Ergonomic rigid internal structure. It  
 houses the heel into the right seat,  
 adjusting the foot support and control  
 of the ankle sideways movements. It  
 keeps the foot tight to the shoe,  
 allowing the perfect fit.


### Torsional stability

#### STABIL•ACTIVE

Support made of rigid plastic  
 material. It stabilizes the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.


### Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,  
 ensuring proven anti-static properties  
 of the footwear over time.


### Other



+ WATERPROOF UPPER

The H-Dry membrane is hydrophilic  
 with high perspiration capacity. It  
 guarantees high performance and  
 durability, facilitating the  
 maintenance of ideal conditions and  
 comfort for the user.


## SRC (SRA+SRB)

SOLE 88 PU - RUBBER		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.34 0.31
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.19 0.15

EN ISO 20344:2011