



EN ISO 20345:2011



POLAR
ELDORADO
ARCTIC GRIP®

89117-15L

S3 HRO HI WR CI SRC

Size: 38-48
Weight: 810 gr.

Fit: 11

Working Environment:
Cold places, Wood-metal carpentry, Mountains, Building



FEATURES

UPPER

Pu Hydro Coated Leather 1,8-2,0 mm
Full Grain-Anilina Leather-Hydro 1,8-2,0 mm
Reflex insert

LINING

3D Air circulation 320 gr.
GenuineWool Polar

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU-RUBBER VIBRAM- ARCTIC GRIP

New polymer blend with an advanced filler system. Engineered for low temperature use. Improved grip on ice or snow. VIBRAM performance, quality and durability. Self-cleaning outsole, designed to all types of ground better. With scaff cap.


TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.

Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



SRC (SRA+SRB)



SOLE 89 PU-RUBBER ARCTIC GRIP		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.62 0.59
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.22 0.20

EN ISO 20344:2011

Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.

