



EN ISO 20345:2011



POLAR  
**ELDORADO  
HDry®**

**88117-10L**
**S3 \*CI HRO HI WR SRC**
**Size:** 38-48  
**Weight:** 855 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Engineering, Farming and  
Gardening


## FEATURES

### UPPER

 Full Grain-Anilina Leather-Hydro  
1,8-2,0 mm  
Reflex insert

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

#### PU-RUBBER VIBRAM-HRO-SRC

 Sole resistant to 300°C by contact.  
With scaff cap and compound  
designed with VIBRAM for stability  
and grip performance. Outsole  
designed to strike the ground  
better and to improve self-  
cleaning. With anti-wear scaff cap.


## TECHNOLOGIES

### Removable Insole

#### 337 climaction fit

 Removable anatomic and ergonomic  
insole. Absorbent and transpiring  
open-cell foam support. Keeps feet  
fresh. Specifically-designed  
thermoforming for exceptional  
comfort.


### Protection elements


 Composite toe cap with fiberglass.  
Resistant to over 200J. Non metal  
perforation resistant insert to over  
1100 N with a 3.0 mm truncated cone  
nail. Protection over the entire sole of  
the foot. Flexible and comfortable


### Lateral stability

#### dynamic HC control technology

 Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.


### Torsional stability

#### STABIL•ACTIVE

 Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.


### Electrical features



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,  
ensuring proven anti-static properties  
of the footwear over time.


### Other


 The HDry membrane is hydrophilic  
with high perspiration capacity. It  
guarantees high performance and  
durability, facilitating the  
maintenance of ideal conditions and  
comfort for the user.


## SRC (SRA+SRB)


 SOLE 88  
PU - RUBBER

TEST	FLAT (CONTACT ANGLE 1°)	HEEL (CONTACT ANGLE 1°)
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	≥0.32	≥0.28
<b>SRB</b> STEEL + GLYCEROL	≥0.18	≥0.13

EN ISO 20344:2011