



EN ISO 20344:2011



POLAR
MONTANA

89156-36

S2 HRO HI CI SRC

Size: 36-48
Weight: 790 gr.

Fit: 11

Working Environment:
Cold places, Food and Chemical industry, Special



FEATURES

UPPER
MicroFiber XPRO 1,8-2,0 mm

LINING
Coagulated PU PrimaLoft® insulation for footwear, made with up to 100% post-consumer recycled content, is specifically designed for the rigors of repeated wear and extreme conditions, providing protection from cold and wet weather under compression

ANTISLIP LINING
DUALMICRO

INSOLE
Dual insulation

TOE CAP
Fiber cap SXT

TYPE
Half-knee Boot

SOLE
PU-RUBBER VIBRAM- ARCTIC GRIP
New polymer blend with an advanced filler system. Engineered for low temperature use. Improved grip on ice or snow. VIBRAM performance, quality and durability. Self-cleaning outsole, designed to all types of ground better. With scaff cap.

TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Protection elements



Composite toecap, reinforced with fiberglass. Structure with a variable thickness for better performances



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.




Electrical features



Wire Electricity Discharge


Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



PrimaLoft® insulation for footwear, made with up to 100% post-consumer recycled content, is specifically designed for the rigors of repeated wear and extreme conditions, providing protection from cold and wet weather under compression



SRC (SRA+SRB)

		SOLE 89 PU - RUBBER ARCTIC GRIP
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.62
	HEEL (CONTACT ANGLE °) ≥0.28	0.59
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.22
	HEEL (CONTACT ANGLE °) ≥0.13	0.20

EN ISO 20344:2011