



EN ISO 20345:2011



POLAR  
**ROLING**  
89374-01L

**S3 HRO HI CI SRC**

**Size:** 38-48  
**Weight:** 800 gr.

**Fit:** 11

**Working Environment:**  
Cold places, Building, Mountains,  
Farming and Gardening



## FEATURES

### UPPER

Grain leather Hydro 1,8-2,0 mm  
Reflex insert  
Full Grain leather Hydro

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

#### PU-RUBBER VIBRAM- ARCTIC GRIP

New polymer blend with an advanced filler system. Engineered for low temperature use. Improved grip on ice or snow. VIBRAM performance, quality and durability. Self-cleaning outsole, designed to all types of ground better. With scaff cap.

## TECHNOLOGIES


### Removable Insole

**337**  
**climaction fit**

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



### Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Lateral stability

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**  
Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other



**FIT TO GO FURTHER™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.



## SRC (SRA+SRB)

SOLE 89 PU - RUBBER ARCTIC GRIP		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.62 0.59
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.22 0.20

EN ISO 20344:2011