



EN ISO 20345:2011

POLAR
ROLING
89374-01L

S3 HRO HI CI SRC

Size: 38-48
Weight: 800 gr.

Fit: 11

Working Environment:
 Cold places, Building, Mountains, Farming and Gardening



FEATURES

UPPER
 Grain leather Hydro 1,8-2,0 mm
 Reflex insert
 Full Grain leather Hydro

LINING
 3D Air circulation 320 gr.

ANTISLIP LINING
 DUALMICRO


INSOLE
 Climaction-Fit 337

TOE CAP
 Fiber cap SXT

RESISTANCE TO PERFORATION
 KX Antiperforation PS

TYPE
 Ankle boot

SOLE
PU-RUBBER VIBRAM- ARCTIC GRIP
 New polymer blend with an advanced filler system. Engineered for low temperature use. Improved grip on ice or snow. VIBRAM performance, quality and durability. Self-cleaning outsole, designed to all types of ground better. With scaff cap.



SRC (SRA+SRB)

SOLE 89
PU - RUBBER ARCTIC GRIP

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL (CONTACT ANGLE °) ≥ 0.28	0.62
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL (CONTACT ANGLE °) ≥ 0.13	0.22

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole
337 climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.

Protection elements

KX RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability
dynamicHC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features
WED
 Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Other
BOA FIT TO GO FURTHER.™

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.