




EN ISO 20345:2011 



POLAR
STELVIO
88087-17L

S3 *CI HRO HI WR SRC

Size: 38-48
Weight: 865 gr.

Fit: 11

Working Environment:
 Building, Farming and Gardening,
 Mountains, Wood-metal
 carpentry

 **HDry** 



FEATURES

- UPPER**
 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Reflex insert
 Full Grain leather Hydro
- LINING**
 3D Air circulation 320 gr.
- ANTISLIP LINING**
 DUALMICRO
- INSOLE**
 Climaction-Fit 337
- TOE CAP**
 Fiber cap SXT
- RESISTANCE TO PERFORATION**
 Textile resistant to 3.0 mm nail
- TYPE**
 Ankle boot

SOLE
PU-RUBBER VIBRAM-HRO-SRC
 Sole resistant to 300°C by contact.
 With scaff cap and compound
 designed with VIBRAM for stability
 and grip performance. Outsole
 designed to strike the ground
 better and to improve self-
 cleaning. With anti-wear scaff cap.



SRC (SRA+SRB)

		SOLE 88 PU - RUBBER
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.34
		0.31
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19
		0.15

EN ISO 20345:2011

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements
 **RESISTANT TO 3.0 mm. NAILS** **fibercap sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
 Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUALMICRO DUALWICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.