sixton SAFETY SHOES peak

EN ISO 20345:2011

POLAR

STELVIO

88087-13L

S3 HRO HI WR CI SRC

Size: 38-48
Weight: 865 gr.

Fit: 11

Working Environment:
Building, Farming and Gardening, Mountains, Cold places

FEATURES

UPPER
Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Reflex insert
Full Grain leather Hydro

LINING
PrimaLoft® Footwear keeps your feet dry at all times, warm and comfortable, even in wet condition.The specially treated and water resistant fibers form a dynamic insulation structure, and the multi-diameter fibers build resiliency.

ANTISLIP LINING
DUALMICRO

INSOLE
Dual insulation

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
Textile resistant to 3.0 mm nail

TYPE
Ankle boot

SOLE
PU-RUBBER VIBRAM-HRO-SRC
Sole resistant to 300°C by contact. With scaff cap and compound designed with VIBRAM for stability and grip performance. Outsole designed to strike the ground better and to improve self-cleaning. With anti-wear scaff cap.

S E FO A WRU P WR HRO HI CI SRC

SRC (SRA+SRB)

SOLE 88
PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.34
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.31
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.15

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

DUAL INSULATION

Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.

Protection elements

RESISTANT TO 3.0 mm. NAILS

fibercap SXT

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features

WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Other

PRIMALOFT

Padding with hi-tech yarns, light and efficient in keeping feet warm and dry. For particularly cold places.



Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale

Maspica Srl a Socio Unico Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it