



EN ISO 20345:2022


 POLAR
STELVIO
88087-13L
S7S FO HI HRO *CI SC LG SR
Size: 38-48
Weight: 865 gr.

Fit: 11

Working Environment:
 Building, Farming and Gardening,
 Mountains, Cold places


FEATURES

UPPER

 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Reflex insert
 Full Grain leather Hydro

LINING

 PrimaLoft® insulation for
 footwear, made with up to 100%
 post-consumer recycled content,
 is specifically designed for the
 rigors of repeated wear and
 extreme conditions, providing
 protection from cold and wet
 weather under compression

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation 2.0

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU-RUBBER VIBRAM-HRO-SRC

 Sole resistant to 300°C by contact.
 With scaff cap and compound
 designed with VIBRAM for stability
 and grip performance. Outsole
 designed to strike the ground
 better and to improve self-
 cleaning. With anti-wear scaff cap.

TECHNOLOGIES

Removable Insole


 The ideal insole in recycled material
 for footwear with "CI" cold protection.
 The presence of felt with an
 "aluminized" film for bottom
 insulation keeps the foot dry and
 warm.


Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

fibercap sxt

 Composite toecap with fiberglass.
 Resistant to over 200J. Non metal
 perforation resistant insert to over
 1100 N with a 3.0 mm truncated cone
 nail. Protection over the entire sole of
 the foot. Flexible and comfortable


Lateral stability

dynamic HC control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability


STABIL-ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.



Electrical features



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other


 PrimaLoft® insulation for footwear,
 made with up to 100% post-consumer
 recycled content, is specifically
 designed for the rigors of repeated
 wear and extreme conditions,
 providing protection from cold and
 wet weather under compression


PU - RUBBER



SOLE 88

SLIP RESISTANCE

EN ISO 20344:2021


BASIC

CERAMIC WITH NALS

FORWARD HEEL SLIP ≥ 0.31	0,48	
BACKWARD FOREPART SLIP ≥ 0.36	0,53	

SR

CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,20	
BACKWARD FOREPART SLIP ≥ 0.22	0,23	