



EN ISO 20345:2011



POLAR
TERRANOVA

88128-10L

S3 HRO HI WR CI SRC

Size: 38-48
Weight: 890 gr.

Fit: 11

Working Environment:
Building, Farming and Gardening,
Mountains, Cold places



FEATURES

UPPER

Full Grain-Anilina Leather-Hydro
1,8-2,0 mm
Full Grain leather Hydro

LINING

PrimaLoft® insulation for footwear, made with up to 100% post-consumer recycled content, is specifically designed for the rigors of repeated wear and extreme conditions, providing protection from cold and wet weather under compression

INSOLE

Dual insulation

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

SOLE

PU-RUBBER VIBRAM-HRO-SRC

Sole resistant to 300°C by contact. With scaff cap and compound designed with VIBRAM for stability and grip performance. Outsole designed to strike the ground better and to improve self-cleaning. With anti-wear scaff cap.


TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.

Protection elements



Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



SRC (SRA+SRB)



SOLE 88
PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.34 0.31
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.15

EN ISO 20345:2011

Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Other



+WATERPROOF UPPER

The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.

