



EN ISO 20345:2011



POLAR  
**TERRANOVA**  
88128-10L

**S3 HRO HI WR CI SRC**

**Size:** 38-48  
**Weight:** 890 gr.

**Fit:** 11

**Working Environment:**  
Building, Farming and Gardening,  
Mountains, Cold places



**FEATURES**

**UPPER**

Full Grain-Anilina Leather-Hydro  
1,8-2,0 mm  
Full Grain leather Hydro  
Soft Full Grain Leather Hydro

**LINING**

PrimaLoft® insulation for footwear, made with up to 100% post-consumer recycled content, is specifically designed for the rigors of repeated wear and extreme conditions, providing protection from cold and wet weather under compression

**INSOLE**

Dual insulation 2.0

**TOE CAP**

Fiber cap SXT

**RESISTANCE TO PERFORATION**

KX Antiperforation PS

**TYPE**

Winter boots

**SOLE**

**PU-RUBBER VIBRAM-HRO-SRC**

Sole resistant to 300°C by contact. With scaff cap and compound designed with VIBRAM for stability and grip performance. Outsole designed to strike the ground better and to improve self-cleaning. With anti-wear scaff cap.

**TECHNOLOGIES**


**Removable Insole**



The ideal insole in recycled material for footwear with "CI" cold protection. The presence of felt with an "aluminized" film for bottom insulation keeps the foot dry and warm.



**Protection elements**



Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**



The H2Dry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.



**SRC (SRA+SRB)**

		SOLE 88 <b>PU - RUBBER</b>
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.34</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.19</b>

EN ISO 20344:2011