



EN ISO 20344:2011



POLAR
TERRANOVA
88128-13L

SB E P WRU HRO HI WR CI SRC

Size: 38-48
Weight: 890 gr.

Fit: 11

Working Environment:
Building, Farming and Gardening,
Mountains, Cold places



FEATURES

UPPER

Full Grain-Anilina Leather-Hydro
1,8-2,0 mm
Full Grain leather Hydro
Soft Full Grain Leather Hydro

LINING

PrimaLoft® insulation for footwear, made with up to 100% post-consumer recycled content, is specifically designed for the rigors of repeated wear and extreme conditions, providing protection from cold and wet weather under compression

INSOLE

Dual insulation 2.0

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Winter boots

SOLE

PU-RUBBER VIBRAM-ICETREK-SRC

New ICETREK compound designed with VIBRAM for stability and grip performance on icy ground. Resistant to 300°C by contact. Self-cleaning outsole, designed to challenge all types of ground better. With anti-wear scaff cap.

TECHNOLOGIES


Removable Insole



The ideal insole in recycled material for footwear with "CI" cold protection. The presence of felt with an "aluminized" film for bottom insulation keeps the foot dry and warm.



Protection elements



Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.




Electrical features

NOT ANTI-STATIC Not anti-static shoe

Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)



SOLE 88
PU - RUBBER
ICE TREK

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.50
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.22
	HEEL (ISO CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011