



EN ISO 20345:2022



RESOLUTE ANVERSA 45527-00L

S3S FO HI *CI M SC HRO SR
Size: 36-48
Weight: 760 gr.

Fit: 11

Working Environment:
 Building, Wood-metal carpentry,
 Engineering, Special


FEATURES

UPPER

 Full Grain leather Hydro 1,8-2,0 mm
 Reflex insert

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

**PU-RUBBER VIBRAM ECOSTEP
PRO-HRO-SR**

 Sole with anti-wear scaff cap.
 Outsole in VIBRAM RECYCLED (≥30%) rubber, resistant to 300° C by contact (HRO), to oils. Design with self-cleaning outsole, with SR Antislip standard.

TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamicControl
 technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



Torsional stability

metatarsal protection

D30 anatomical protection, resistant up to 100 Joules, to protect the metatarsal against falling metal sheets or similar



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



Outsole in RECYCLED VIBRAM (≥30%) with SR Antislip standard. D30 materials are made using a combination of advanced polymer chemistry and cutting-edge science, cushioning and anti-fatigue effect.



PU - RUBBER

SOLE 45

SLIP RESISTANCE

EN ISO 20344:2021

BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP ≥ 0.31	0,45	
BACKWARD FOREPART SLIP ≥ 0.36	0,47	

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,28	
BACKWARD FOREPART SLIP ≥ 0.22	0,25	