



EN ISO 20345:2022



RESOLUTE ANVERSA BOA 45553-00L

S7S FO HI *CI SC HRO SR
Size: 36-48
Weight: 760 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Engineering, Special


FEATURES

UPPER

Full Grain leather Hydro 1,8-2,0 mm
Reflex insert

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Ankle boot

SOLE

**PU-RUBBER VIBRAM ECOSTEP
PRO-HRO-SR**

Sole with anti-wear scaff cap.
Outsole in VIBRAM RECYCLED
(≥30%) rubber, resistant to 300° C
by contact (HRO), to oils. Design
with self-cleaning outsole, with SR
Antislip standard.

Boa® lace length
L+1 - 115cm

TECHNOLOGIES

Removable Insole

QRS02 GREEN

Anatomical breathable insole.
Resistant fabric with recycled open-
cell foam that absorbs shocks and
reduces fatigue. Eliminates sweat
with its high ability to evaporate it.
Continuous comfort for months and
months of use


Protection elements

KX GREEN RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toecap with fiberglass.
Resistant to over 200J. Recycled non
metal perforation resistant insert to
over 1100 N with a 3.0 mm truncated
cone nail. Protection over the entire
sole of the foot. Flexible and
comfortable


Lateral stability

dynamicHC control
technology

Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.


Torsional stability

metatarsal protection

D30 anatomical protection, resistant
up to 100 Joules, to protect the
metatarsal against falling metal
sheets or similar


Electrical features


ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other


The HDry membrane is hydrophilic
with high perspiration capacity. It
guarantees high performance and
durability, facilitating the
maintenance of ideal conditions and
comfort for the user.


PU - RUBBER

SOLE 45

SLIP RESISTANCE

EN ISO 20344:2021

BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP ≥ 0.31	0,45	
BACKWARD FOREPART SLIP ≥ 0.36	0,47	

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,28	
BACKWARD FOREPART SLIP ≥ 0.22	0,25	