



EN ISO 20345:2011


**RESOLUTE
FORZA BOA®
43460-07L**
S3 SRC *CI AVAILABLE
Size: 36-48
Weight: 610 gr.

Fit: 11

Working Environment:
 Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas

FEATURES
TOMAIA

 MicroFiber Rubber 1,8-2,0 mm
 MicroFiber Rubber with Scratch Bumper 1,8-2,0 mm
 MicroFiber Rubber 1,8-2,0 mm

FODERA

3D Green Air 320 gr.

**FOD. ANTISCIIVOLO
DUALMICRO**
**SUOLETTA
Qrs01**
PUNTALE

Fiber cap SXT

**RESISTENZA ALLA
PERFORAZIONE**

KX Antiperforation PS

TIPOLOGIA

Low Shoe


SUOLA
PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

Lunghezza filo Boa®
 L6 - 85cm

TECNOLOGIE
Suoletta Intercambiabile


Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use


Elementi di Protezione


Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable


Stabilità Trasversale


Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.


Stabilità Torsione


Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.


Caratteristiche Elettriche


ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Altro


D30 materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.


SRC (SRA+SRB)

 SOLE 43
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.39
	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.24
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.24
	FLAT ≥0.13 HEEL (CONTACT ANGLE °) ≥0.13	0.23

EN ISO 20344:2011