



EN ISO 20345:2022



RESOLUTE
FORZA BOA
45460-15L

S7S FO HI *CI SC HRO SR

Size: 36-48
Weight: 660 gr.

Fit: 11

Working Environment:
Multipurpose, Logistics and Light Industry, Components and Automotive



FEATURES

UPPER
Mesh H.T. no ladder
Full Grain leather Hydro 1,8-2,0 mm

LINING
3D Green Air 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
QRS02 Green

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
KX recycled insert - PS method

TYPE
Low Shoe

SOLE
PU-RUBBER VIBRAM ECOSTEP PRO-HRO-SR
Sole with anti-wear scaff cap. Outsole in VIBRAM RECYCLED ($\geq 30\%$) rubber, resistant to 300° C by contact (HRO), to acids and oils. Design with self-cleaning outsole, with SR Antislip standard.

Boa® lace length
L6 - 85cm

TECHNOLOGIES

Removable Insole
QRS02 GREEN
Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements
KX RESISTANT TO 3.0 mm. NAILS **fibercap sxt**
Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

ESD
ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

D3O **PROGRESSIVE CUSHIONING AND ADAPTIVE STABILITY**
D3O materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.



PU - RUBBER		SLIP RESISTANCE	
SOLE 45		EN ISO 20344:2021	
BASIC CERAMIC WITH NAILS	FORWARD HEEL SLIP ≥ 0.31	0,45	
	BACKWARD FOREPART SLIP ≥ 0.36	0,47	
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,28	
	BACKWARD FOREPART SLIP ≥ 0.22	0,25	