



EN ISO 20345:2022


RESOLUTE
FORZA BOA
45460-15L
S7S FO HI *CI SC HRO SR
Size: 36-48
Weight: 660 gr.

Fit: 11

Working Environment:
 Multipurpose, Logistics and Light Industry, Components and Automotive


FEATURES

UPPER

 Mesh H.T. no ladder
 Full Grain leather Hydro 1,8-2,0 mm

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Low Shoe

SOLE
PU-RUBBER VIBRAM ECOSTEP
PRO-HRO-SR

 Sole with anti-wear scaff cap.
 Outsole in VIBRAM RECYCLED (≥30%) rubber, resistant to 300° C by contact (HRO), to oils. Design with self-cleaning outsole, with SR Antislip standard.

Boa® lace length
 L6 - 85cm

TECHNOLOGIES

Removable Insole


Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use


Protection elements


Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable


Lateral stability
dynamic H^C control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.


Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.


Electrical features


ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other


Outsole in RECYCLED VIBRAM (≥30%) with SR Antislip standard. D30 materials are made using a combination of advanced polymer chemistry and cutting-edge science, cushioning and anti-fatigue effect.


PU - RUBBER

SOLE 45

SLIP RESISTANCE

EN ISO 20344:2021

BASIC
 CERAMIC WITH NALS

FORWARD HEEL SLIP ≥ 0.31	0,45
BACKWARD FOREPART SLIP ≥ 0.36	0,47

SR
 CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,28
BACKWARD FOREPART SLIP ≥ 0.22	0,25