



EN ISO 20345:2022



RESOLUTE FORZA HIGH BOA 45477-13L

S7S FO HI CI SC HRO SR
Size: 36-48
Weight: 670 gr.

Fit: 11

Working Environment:
 Multipurpose, Logistics and Light
 Industry, Components and
 Automotive, ESD Areas


FEATURES

UPPER

 Full Grain leather Hydro 1,8-2,0
 mm
 Mesh H.T. no ladder

LINING

 GenuineWool Polar
 GenuineWool Polar

INSOLE

Dual insulation 2.0

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Ankle boot

SOLE

**PU-RUBBER VIBRAM ECOSTEP
PRO-HRO-SR**

 Sole with anti-wear scaff cap.
 Outsole in VIBRAM RECYCLED
 (≥30%) rubber, resistant to 300° C
 by contact (HRO), to oils. Design
 with self-cleaning outsole, with SR
 Antislip standard.

Boa® lace length
 L+1 - 115cm

TECHNOLOGIES

Removable Insole


 The ideal insole in recycled material
 for footwear with "CI" cold protection.
 The presence of felt with an
 "aluminized" film for bottom
 insulation keeps the foot dry and
 warm.


Protection elements


 Composite toecap with fiberglass.
 Resistant to over 200J. Non metal
 perforation resistant insert to over
 1100 N with a 3.0 mm truncated cone
 nail. Protection over the entire sole of
 the foot. Flexible and comfortable


Lateral stability

**dynamic HC control
technology**

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

 Support made of rigid plastic
 material. It supports the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other


 The H-Dry membrane is hydrophilic
 with high perspiration capacity. It
 guarantees high performance and
 durability, facilitating the
 maintenance of ideal conditions and
 comfort for the user.


PU - RUBBER

SOLE 45

SLIP RESISTANCE

EN ISO 20344:2021

BASIC
 CERAMIC WITH
 NALS

FORWARD HEEL SLIP ≥ 0.31	0,45
BACKWARD FOREPART SLIP ≥ 0.36	0,47

SR
 CERAMIC WITH
 GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,28
BACKWARD FOREPART SLIP ≥ 0.22	0,25