



EN ISO 20345:2011



RESOLUTE  
**FORZA HIGH  
DIELECTRIC**

43469-03L

**SB E FO P WRU SRC \*CI  
AVAILABLE**

**Size:** 36-48  
**Weight:** 650 gr.

**Fit:** 11

**Working Environment:**  
Electrical risk-Electrician



**FEATURES**

**UPPER**

MicroFiber Suede 1,8-2,0 mm  
Mesh H.T. no ladder

**LINING**

3D Green Air 320 gr.

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

Qrs01 Dielectric

**TOE CAP**

Fiber cap SXT

**RESISTANCE TO PERFORATION**

Non conductive Textile resistant  
to 3.0 mm nail - X Method

**TYPE**

Ankle boot

**SOLE**

**PU / PU DIELECTRIC SRC**

Double density PU sole, Outer- and  
in-between sole with dielectric  
compound. Light and comfortable,  
very versatile, highly non-slip SRC  
Antislip standard. Not to be used in  
places with explosives or gas.

**TECHNOLOGIES**

**Removable Insole**



Non-conductive anatomical  
breathable insole. Resistant fabric  
with recycled open-cell foam that  
absorbs shocks and reduces fatigue.  
Eliminates sweat with its high ability  
to evaporate it. Continuous comfort  
for months and months of use

**Protection elements**



Composite toecap with fiberglass.  
Resistant to over 200J. Non metal  
perforation resistant insert to over  
1100 N with a 3.0 mm truncated cone  
nail. Protection over the entire sole of  
the foot. Flexible and comfortable



**Lateral stability**

dynamic **HC** control  
technology

Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.



**Torsional stability**

**STABIL•ACTIVE**

Support made of rigid plastic  
material. It supports the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



**SRC (SRA+SRB)**



SOLE 43  
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.39
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.24
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011



**Electrical features**



ELECTRIC SHOCK RESISTANT sole -  
CSA Z195-14 standard Method-  
Tested at 18000 V in dry conditions;  
max voltage 1.0 mA. Secondary  
protective equipment to be added to  
primary protective equipment. Not to  
be used in places with explosives or  
gas.



**Other**



D30 materials are made using a  
combination of advanced polymer  
chemistry and cutting-edge science.  
It absorbs and dissipates energy  
during and impact, with superior  
stability, cushioning and anti-fatigue  
effect.

