



EN ISO 20344:2011



RESOLUTE
FORZA
43452-05L

S1P SRC

Size: 36-48
Weight: 600 gr.

Fit: 11

Working Environment:
Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas



FEATURES

UPPER
MicroFiber Suede 1,8-2,0 mm

LINING
3D Green Air 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Qrs01

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
KX Antiperforation PS

TYPE
Low Shoe

SOLE
PU / PU ESD-PLUS SRC
Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

TECHNOLOGIES


Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



D30 materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.



SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.39
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.24
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011