



EN ISO 20345:2011


RESOLUTE
FORZA
43452-13L
S3 SRC *CI AVAILABLE
Size: 36-48
Weight: 600 gr.

Fit: 11

Working Environment:
 Multipurpose, Logistics and Light
 Industry, Components and
 Automotive, ESD Areas


CARATTERISTICHE

UPPER

 MicroFiber Rubber with Scratch
 Bumper 1,8-2,0 mm

LINING

3D Green Air 320 gr.

ANTISLIP LINING
 DUALMICRO

INSOLE

Qrs01

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU / PU ESD-PLUS SRC

 Double density PU sole, Outer- and
 in-between sole with ESD
 compound. For use in contact with
 sensitive electronic equipment.
 Light and comfortable, very
 versatile, highly non-slip SRC
 Antislip standard.

TECHNOLOGIES

Removable Insole


 Anatomical breathable insole.
 Resistant fabric with recycled open-
 cell foam that absorbs shocks and
 reduces fatigue. Eliminates sweat
 with its high ability to evaporate it.
 Continuous comfort for months and
 months of use


Protection elements


 Composite toecap with fiberglass.
 Resistant to over 200J. Non metal
 perforation resistant insert to over
 1100 N with a 3.0 mm truncated cone
 nail. Protection over the entire sole of
 the foot. Flexible and comfortable


Lateral stability

dynamic HC control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

 Support made of rigid plastic
 material. It supports the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other

D30
 PROGRESSIVE CUSHIONING
 AND ADAPTIVE STABILITY

 D30 materials are made using a
 combination of advanced polymer
 chemistry and cutting-edge science.
 It absorbs and dissipates energy
 during and impact, with superior
 stability, cushioning and anti-fatigue
 effect.


SRC (SRA+SRB)



SOLE 43 PU - PU		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.39
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.24
		0.23

EN ISO 20344:2011