



EN ISO 20345:2011



## RESOLUTE RAPIDO 43478-03L

**S3 SRC \*CI AVAILABLE**
**Size:** 36-48  
**Weight:** 710 gr.

**Fit:** 11

**Working Environment:**  
 Multipurpose, Farming and  
 Gardening, Oil industry, ESD  
 Areas


## FEATURES

### UPPER

 MicroFiber Rubber 1,8-2,0 mm  
 No ladder H.T. Fabric  
 MicroFiber Rubber with Scratch  
 Bumper 1,8-2,0 mm

### LINING

3D Green Air 320 gr.

### ANTISLIP LINING DUALMICRO

### INSOLE

Qrs01

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Half-knee Boot

### SOLE

#### PU / PU ESD-PLUS SRC

 Double density PU sole, Outer- and  
 in-between sole with ESD  
 compound. For use in contact with  
 sensitive electronic equipment.  
 Light and comfortable, very  
 versatile, highly non-slip SRC  
 Antislip standard.

## TECHNOLOGIES

### Removable Insole


 Anatomical breathable insole.  
 Resistant fabric with recycled open-  
 cell foam that absorbs shocks and  
 reduces fatigue. Eliminates sweat  
 with its high ability to evaporate it.  
 Continuous comfort for months and  
 months of use


### Protection elements


 Composite toecap with fiberglass.  
 Resistant to over 200J. Non metal  
 perforation resistant insert to over  
 1100 N with a 3.0 mm truncated cone  
 nail. Protection over the entire sole of  
 the foot. Flexible and comfortable


### Lateral stability


 Ergonomic rigid structure. It  
 accommodates the heel, adjusting the  
 foot support and control of the ankle  
 in sideways movements. The plastic  
 material increases protection of the  
 ankle against sharp or pointy objects.


### Torsional stability


 Support made of rigid plastic  
 material. It supports the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.


### Electrical features


 ESD footwear discharge static  
 electricity and avoid damaging  
 surrounding objects; they are  
 designed in compliance with the  
 following standards: IEC EN  
 61340-5-1:2016 - IEC EN  
 61340-4-3:2018 - IEC EN  
 61340-4-5:2018.

### Other


 D30 materials are made using a  
 combination of advanced polymer  
 chemistry and cutting-edge science.  
 It absorbs and dissipates energy  
 during and impact, with superior  
 stability, cushioning and anti-fatigue  
 effect.


## SRC (SRA+SRB)


 SOLE 43  
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.39
	HEEL (CONTACT ANGLE °°) ≥0.28	0.40
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.24
	HEEL (CONTACT ANGLE °°) ≥0.13	0.23

EN ISO 20344:2011