



EN ISO 20345:2011


**RESOLUTE**  
**SALT0**  
**43455-00L**
**S1P SRC**
**Size:** 36-48  
**Weight:** 610 gr.

**Fit:** 11

**Working Environment:**  
 Multipurpose, Wood-metal  
 carpentry, Components and  
 Automotive, ESD Areas


## FEATURES

### UPPER

 MicroFiber Suede 1,8-2,0 mm  
 SpiderMesh HT

### LINING

3D Green Air 320 gr.

**ANTISLIP LINING**  
 DUALMICRO

### INSOLE

Qrs01

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Sandal

### SOLE

**PU / PU ESD-PLUS SRC**

 Double density PU sole, Outer- and  
 in-between sole with ESD  
 compound. For use in contact with  
 sensitive electronic equipment.  
 Light and comfortable, very  
 versatile, highly non-slip SRC  
 Antislip standard.

## TECHNOLOGIES

### Removable Insole


 Anatomical breathable insole.  
 Resistant fabric with recycled open-  
 cell foam that absorbs shocks and  
 reduces fatigue. Eliminates sweat  
 with its high ability to evaporate it.  
 Continuous comfort for months and  
 months of use

### Protection elements


 Composite toecap with fiberglass.  
 Resistant to over 200J. Non metal  
 perforation resistant insert to over  
 1100 N with a 3.0 mm truncated cone  
 nail. Protection over the entire sole of  
 the foot. Flexible and comfortable

### Lateral stability

**dynamic HC control**  
 technology

 Ergonomic rigid internal structure. It  
 houses the heel into the right seat,  
 adjusting the foot support and control  
 of the ankle sideways movements. It  
 keeps the foot tight to the shoe,  
 allowing the perfect fit.

### Torsional stability

**STABIL•ACTIVE**

 Support made of rigid plastic  
 material. It supports the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.


## SRC (SRA+SRB)



SOLE 43 PU - PU		
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	<b>0.39</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	<b>0.24</b>
		<b>0.23</b>

EN ISO 20344:2011

### Electrical features


 ESD footwear discharge static  
 electricity and avoid damaging  
 surrounding objects; they are  
 designed in compliance with the  
 following standards: IEC EN  
 61340-5-1:2016 - IEC EN  
 61340-4-3:2018 - IEC EN  
 61340-4-5:2018.

### Other


 D30 materials are made using a  
 combination of advanced polymer  
 chemistry and cutting-edge science.  
 It absorbs and dissipates energy  
 during and impact, with superior  
 stability, cushioning and anti-fatigue  
 effect.
