



EN ISO 20345:2011



RESOLUTE

TEMPRA

43461-00 S1 SRC

Size: 36-48 Weight: 550 gr.

Fit: 11

Working Environment:

Multipurpose, Logistics and Light Industry, Food and Chemical industry, ESD Areas











FEATURES

UPPER

MicroFiber Suede 1,8-2,0 mm Reflex insert Recycled Digitex Airy

3D Green Air 320 gr.

ANTISLIP LINING

QRS02 Green

TYPE

Low Shoe

SOLE

PU/PUESD-PLUSSRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled opencell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Lateral stability

dynamic H control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Protection elements

fibercap **SXt**

Composite toecap, reinforced with fiberglass. Structure with a variable thickness for better performances



Torsional stability



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



GREEN SOLUTION

The green proposal by SIXTON PEAK®. RESOLUTE GREEN contains over 40% of GRS certified recycled products with pre and post-consumer origins (ratio calculated on the surface of the upper)



LINING

DUALMICRO

INSOLE

TOE CAP

Fiber cap SXT



SRC (SRA+SRB)

