sixton SAFETY SHOES peak

EN ISO 20345:2011

RESOLUTE

TEMPRA

43461-04L

S3 SRC *CI AVAILABLE

Size: 36-48
Weight: 600 gr.

Fit: 11

Working Environment:
Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas

FEATURES

UPPER
MicroFiber Suede 1,8-2,0 mm
Recycled Digitex Hydro Airy
Reflex insert
Recycled Digitex Hydro Airy

LINING
3D Green Air 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
QRS02 Green

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
KX recycled insert - PS method

TYPE
Low Shoe

SOLE
PU / PU ESD-PLUS SRC
Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

S E FO A WRU P SRC CI AVAILABLE

SRC (SRA+SRB)

SOLE 43
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.39
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.40
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.24
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.23

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

QRS02 GREEN

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use

Protection elements

KX GREEN RESISTANT TO 3.0 mm. NAILS

fibercap SXT

Composite toecap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features

ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

GREEN SOLUTION

The green proposal by SIXTON PEAK®. RESOLUTE GREEN contains over 40% of GRS certified recycled products with pre and post-consumer origins (ratio calculated on the surface of the upper)

Maspica Srl a Socio Unico Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale