



EN ISO 20345:2011



RITMO

BLUES
91186-07L
S1P SRC
Size: 35-48

Weight: 540 gr.

Fit: 11

Working Environment:

ESD Areas, Finishing-off building,
 Components and Automotive,
 Multipurpose


FEATURES

UPPER

Drummed Leather MILLEFORI
 1,6-1,8 mm
 Drummed leather Hydro 1,6-1,8
 mm
 Drummed leather Hydro 1,6-1,8
 mm

LINING

Resistex® Carbon

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and
 in-between sole with ESD
 compound. For use in contact with
 sensitive electronic equipment.
 Light and comfortable, very
 versatile, highly non-slip SRC
 Antislip standard.

TECHNOLOGIES

Removable Insole

FIVE4FIT

Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"


Protection elements

ZERO(k)
 ANTIPERFORATION

alu-sxt2.0
 aluminium

A new aluminium multi-thicknesses
 toecap, which delivers a highly
 performing protection where needed.
 Resistant to impact of over 200J. Non
 Metallic anti-perforation insert.
 Resistant to over 1100 N with zero
 perforation.


Lateral stability

dynamic HC control
 technology

Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other

Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


SRC (SRA+SRB)

	SOLE 91 PU - PU	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.54 0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.29 0.23

EN ISO 20344:2011