



EN ISO 20345:2011



RITM0

# CUBAN

91328-03 S1 SRC

Size: 35-48 Weight: 500 gr.

Fit: 11

# Working Environment:

Components and Automotive, Logistics and Light Industry, ESD

Areas





### **FEATURES**

#### **UPPER**

MicroFiber Suede with Pro-tech SXT light 1,6-1,8 mm

3D Air circulation 320 gr.

## **ANTISLIP LINING**

**DUALMICRO** 

### INSOLE

Five 4 Fit

#### TOE CAP

Alu SXT 2.0 Toe cap

#### TYPE

Low Shoe

#### **SOLE**

#### **PU/PUESD-PLUSSRC**

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

#### **TECHNOLOGIES**

#### Removable Insole



Highly breathable and absorbent anatomic insole.Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

#### **Protection elements**



The result of the evolution of the  $latest\,aluminium\,technologies.\,A\,new$ multi-thicknesses to ecap, which delivers a highly performing protection where needed. Ultralight protection, keeping comfortable inner



#### Lateral stability

# dynamic H control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

# Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater



#### **Electrical features**



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

#### Other

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



# SRC (SRA+SRB)

