



EN ISO 20345:2011



RITMO

CUBAN
91328-09L
S3 SRC
Size: 35-48
Weight: 520 gr.

Fit: 11

Working Environment:

 Finishing-off building, Logistics
 and Light Industry, Components
 and Automotive, ESD Areas


FEATURES

UPPER

 MicroFiber Suede 1,6-1,8 mm
 MicroFiber Suede with Pro-tech
 SXT light 1,6-1,8 mm

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE
PU / PU ESD-PLUS SRC

 Double density PU sole, Outer- and
 in-between sole with ESD
 compound. For use in contact with
 sensitive electronic equipment.
 Light and comfortable, very
 versatile, highly non-slip SRC
 Antislip standard.

TECHNOLOGIES

Removable Insole

 Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"

Protection elements

 Toecap "Alu Sxt 2.0" with
 differentiated thicknesses, resistant
 to 200J. Non metal perforation
 resistant Insert to over 1100 N with a
 3.0 mm truncated cone nail. Protection
 over the entire sole of the foot.
 Flexible and comfortable

Lateral stability

 dynamic **HC** control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.

Torsional stability

STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.

Electrical features

 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.

SRC (SRA+SRB)

	SOLE 91 PU - PU	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.54
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.29
		0.23

EN ISO 20344:2011