



EN ISO 20344:2011



RITMO

**DANCE**
**91195-03L**
**S1P SRC**
**Size:** 35-48

**Weight:** 540 gr.

**Fit:** 11

**Working Environment:**

 Finishing-off building, Logistics  
 and Light Industry, Components  
 and Automotive, Multipurpose


## FEATURES

### UPPER

 Drummed Suede Millefori  
 Drummed Suede Leather Hydro  
 1,6-1,8 mm

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Five 4 Fit

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

### TYPE

Low Shoe

### SOLE

#### PU DUAL-DENSITY SRC

 Double density PU outsole with  
 tread designed mainly for indoor  
 use. Self-cleaning design and  
 highly non-slip grip. SRC Antislip  
 standard.

## TECHNOLOGIES

### Removable Insole


 Highly breathable and absorbent  
 anatomic insole. Multilayer structure  
 to take advantage of the peculiarities  
 of each component. Dry and with a  
 comfortable memory foam "pillow"


### Protection elements

**ZERO(k)**

ANTIPERFORATION

**alu-sxt2.0**  
 aluminium

 A new aluminium multi-thicknesses  
 toecap, which delivers a highly  
 performing protection where needed.  
 Resistant to impact of over 200J. Non  
 Metallic anti-perforation insert.  
 Resistant to over 1100 N with zero  
 perforation.


### Lateral stability

**dynamic HC control**  
 technology

 Ergonomic rigid internal structure. It  
 houses the heel into the right seat,  
 adjusting the foot support and control  
 of the ankle sideways movements. It  
 keeps the foot tight to the shoe,  
 allowing the perfect fit.


### Torsional stability


**STABIL•ACTIVE**

 Support made of rigid plastic  
 material. It stabilizes the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.


### Electrical features



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,  
 ensuring proven anti-static properties  
 of the footwear over time.


### Other

**DUALMICRO**  
**DUALMICRO**

 Double non-slip layer of microfibre,  
 resistant up to 200,000 cycles. Makes  
 the footwear more comfortable,  
 blocking the foot during use.


## SRC (SRA+SRB)


 SOLE 91  
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.54
	HEEL (CONTACT ANGLE °°) ≥0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.29
	HEEL (CONTACT ANGLE °°) ≥0.13	0.23

EN ISO 20344:2011