



EN ISO 20344:2011



RITMO  
**DANCE**  
91195-18L

**S3 SRC**

**Size:** 35-48  
**Weight:** 540 gr.

**Fit:** 11

**Working Environment:**  
Finishing-off building, Logistics  
and Light Industry, Components  
and Automotive



## FEATURES

### UPPER

Drummed leather Hydro 1,6-1,8 mm

### LINING

3D Air circulation 320 gr.

**ANTISLIP LINING**  
DUALMICRO

### INSOLE

Five 4 Fit

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

### TYPE

Low Shoe

### SOLE

**PU DUAL-DENSITY SRC**

Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

## TECHNOLOGIES

### Removable Insole

**FIVE4FIT**

Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Protection elements

**ZERO(k)**  
ANTIPERFORATION

**alu-sxt2.0**  
aluminium

A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



### Lateral stability

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features

**WED**

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other

**DUALMICRO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



## SRC (SRA+SRB)

	SOLE 91 PU - PU	
<b>SRA</b> CERAMIC + DIETEGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE 7°) ≥0.28	<b>0.54</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE 7°) ≥0.13	<b>0.29</b>
		<b>0.23</b>

EN ISO 20344:2011