sixton SAFETY SHOES peak

EN ISO 20345:2011

RITMO

DANCE

91195-40L

S3 SRC

Size: 35-48
Weight: 540 gr.

Fit: 11

Working Environment:
Finishing-off building, Logistics and Light Industry, Components and Automotive, ESD Areas

FEATURES

UPPER
Drummed leather Hydro 1,6-1,8 mm
Soft Full Grain Leather Hydro

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Five 4 Fit

TOE CAP
Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION
Textile resistant to 3.0 mm nail – X Method

TYPE
Low Shoe

SOLE
PU / PU ESD-PLUS SRC
Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

S E FO A WRU P SRC

SRC (SRA+SRB)

SOLE 91
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.54
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.29
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.23

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

FIVE4FIT

Highly breathable and absorbent anatomic insole.Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

Protection elements

KX RESISTANT TO 3.0 mm. NAILS

alu-sxt 2.0 aluminium

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features

ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

Maspica Srl a Socio Unico Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale