



EN ISO 20345:2011



RITMO
DANCE
92195-00L

S3 SRC

Size: 35-48
Weight: 510 gr.

Fit: 11

Working Environment:
Finishing-off building, Logistics and Light Industry, Components and Automotive



CARATTERISTICHE

- TOMAIA**
Drummed leather Hydro 1,6-1,8 mm
- FODERA**
3D Air circulation 320 gr.
- FOD. ANTISCIIVOLO**
DUALMICRO
- SUOLETTA**
Five 4 Fit
- PUNTALE**
Alu SXT 2.0 Toe cap
- RESISTENZA ALLA PERFORAZIONE**
Zero(K) Perforation resistant
- TIPOLOGIA**
Low Shoe

SUOLA
PU - TPU (ALU-SXT)
PU-TPU sole The outsole in TPU is more resistant to abrasion, guaranteeing a longer life. The new look enhances lightness, comfort and technical features. SRC Antislip Standard.

TECNOLOGIE

Suoletta Intercambiabile
FIVE 4 FIT
Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



Protection elements
ZERO(k)
ANTIPERFORATION **alu-sxt2.0** aluminium
A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



Lateral stability
dynamic HC control
technology
Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL ACTIVE
Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
Wire Electricity Discharge
Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUAL MICRO DUAL MICRO
Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)

	SOLE 92 PU - TPU	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL (CONTACT ANGLE °) ≥ 0.28	0.40 0.53
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL (CONTACT ANGLE °) ≥ 0.13	0.25 0.15

EN ISO 20344:2011